



Ceiling Ideal

PRODUCT DESCRIPTION

Acrylic copolymer emulsion-based, water based, decorative white ceiling paint for interior surfaces.

SPECIFICATIONS

- ✓ Water based
- ✓ Matte
- ✓ Ideal whiteness-coverage balance
- ✓ Breathable

APPLICATION SURFACES

Fawori Ceiling Ideal is preferred to be used on satin plaster, putty, plasterboard surfaces and old painted or primed interior ceiling surfaces with no dusting behavior.

APPLICATION

Ensure that the application surface is smooth, solid and able to bear the primer and top-coat paint. Clean all types of stain, dust, block grease, loose layers and make the required surface corrections. Observe the setting period (28 days) for concrete, exposed concrete and new plastered surfaces.

Ensure that the ambient and surface temperatures are between +5°C and +30°C during application and until the products are fully dried, and protect the surfaces against frost. Apply using a brush, roller or spray gun.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568. You can access the MSDS and TDS forms including the information regarding detailed application, healthy-safety-handling risks, and precautions on www.fawori.com.

Airless Spraying:

Pressure: 140 bar

Nozzle Angle: 50°

Nozzle Size (inch): 0.019"

Thinning (Water): 10-15 % (Volume)

THINNING

Recommended to be applied in two coats after thinning by 20-25% with clean water in brush and roller applications.

DRYING TIME (at 20°C, 65% RH)

Touch dry: 1 hours

Resting period between coats: 6 hours

Final drying: 24 hours (drying time may increase at higher relative humidity and lower temperature)

CONSUMPTION

Depending on the type, absorbency and structure of the surface to be applied, an area of 7-10 m² can be painted with 1 kilogram in one layer. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

20 kg-17.5 kg-10 kg-3.5 kg



WARNING STATEMENT

Caution

HAZARD STATEMENT

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing its dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international



Complies with TS 5808/2012.



Complies with the G communiqué.

TSE

Wet Scrub Resistance: Class 5

Coverage Strength: Class 2 (7m²/L)

Granule Size: Fine

Gloss: Matte

This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev1 March 2020